

Apollo/Apollo Pro

High End Desktop Barcode Printer

Advanced thermal transfer desktop barcode printer with 300m ribbon supported





Characteristic

- High-speed printing up to 8 ips with top-level TPH
- Automatically identifies the resolution from 203DPI / 300DPI
- The modular design of printer head makes the maintenance easy
- With 128MB DDR2 RAM, 256MB Flash and USB HOST interface
- Dual-wall frame, robust and sturdy structure



The Details Show



Specification

Item		Apollo	Apollo Pro
Printing	Printing Method	Direct thermal/Thermal transfer	
	Resolution	203 DPI / 300 DPI	
	Max. Printing Speed	8 ips(203 DPI) / 6 ips(300 DPI)	
	Max. Printing Width	108 mm(203 DPI) / 106 mm(300 DPI)	
	Max. Printing Length	2286 mm(203 DPI) / 1524 mm(300 DPI)	
CPU		32-bit RISC CPU	
Memory	RAM	128MB	
	Flash	256MB	
Detection	Sensor	Out-of-paper detection, gap detection, ribbon detection, black mark detection, cover-opening detection	
Media	Types	Black mark label, punched hole label, folding or rolling die cutting label	
	Width	1" (25.4mm) – 4.33" (110mm)	
	Height	0.31" (8mm)– 9.84" (250mm)	
	Thickness	0.002"(60um)-0.08"(200um)	
	Label Roll Diameter	5"(127 mm) Max	
	Core Diameter	0.5"(12.7 mm), 1"(25.4 mm), 1.5"(38 mm)	
Ribbon	Type	Wax, Wax/Resin, Resin	
	Width	2" (50mm) – 4.38" (118mm)	
	Length	984.2' (300 m)	
	Core Diameter	1"(25.4 mm)	
Programming Language		ZPL, TSPL,EPL,DPL	
Software	Label Design Software	HPRT BarTender Ultralite (professional and higher versions are available for trial)	
	Driver	Seagull Windows Vista7,8,10, Vista, 7, 8, 11	
Resident Fonts	Bitmap fonts	6, 8, 12, 16, 32, OCR A & B. 90°, 180°, 270° rotatable and 10 magnification.	
	TTF fonts	CG Triumvirate™times expandable in horizontal and vertical directions, simplified Chinese.	
Code Pages		DOS437,720,737,755,775,850,852,855,856,857,858,860,862,863,864,865,866, Windows 1250,1251,1252,1253,1254,1255,1256,1257,1258, ISO8859-1,-2,-3,-4,-5,-6,-8,-9,-15	
Barcodes	1D	Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11	
	2D	PDF417, Maxicode, DataMatrix, QR Code, Aztec, CODE49, CODABLOCK,PDF417, Maxicode, DataMatrix, QR Code, Aztec	
Interfaces	Standard	USB, Serial, Ethernet	USB, Serial, Ethernet, USB HOST
	Optional	Wi-Fi or Bluetooth	Wi-Fi or Bluetooth
Control Panel		Two-color status light: power indicator, status indicator Four control buttons: power button, pause button, feed button, cancel button	
Power Supply		Power Switch	
		Input: AC 100-240 V, 50/60 Hz Output: DC 24 V / 2.5 A	
Environment	Operation	41°F(5°C) to 104°F(40°C) , humidity 30% to 85% ,non-condensing	
	Storage	-4°F(-20°C) to 122°F(50°C), humidity 10% to 90% ,non-condensing	
Physical Characteristic	Dimension(L*H*W)	308×250×180mm	
	Weight	2.8 KG	
	User Interface	Five LED lights, four buttons	3.5" Touch Screen, four buttons
Options & Accessory		Peeler module, cutter module, external label roll holder	
Agency Approval		CE,FCC,RoHS	



Xiamen Hanin Co.,Ltd.

Address: 1-5F, NO.8,Gaoqi South 12th Road,Xiamen,China

Telephone: +86-(0)592-5885993 (English)

E-mail: overseas@hpert.com

Website: www.hpert.com

Brochure Version:202402



HPRT Official Website